

Filament Tape

GF0304-138



Weasy

Technical Data Sheet

Product Description



- * Weasy GF0304-138 is mono Filament tape based on a polyester film laminated to fiberglass which has a good tensile strength as well as high adhesion.
- * In moving furniture that contain movable parts such as plastic trays in refrigerators so that there is no damage to these parts during transit. This tape does not leave any glue mark, so the user of products or application can easily remove the tape and without any adhesive residue.
- * Remains good adhesion at wide temperature range (depends on the nature and the weight of the sealing materials).

Product Construction

Backing	Backing Color	Reinforcement	Adhesive
PET film	Clear	Glass yarn	Pressure Sensitive Adhesive

Typical Physical Properties

(21 Degree, stainless steel)

Note: Typical data for reference, not for specification purpose.

		Testing method
Peel adhesion at 180 °	15N/inch	D 3330
Tensile Strength:	170N/inch	D 3759
Elongation at Break:	15%	D 3759
Holding Power:	>72h	D 3654
Total Thickness:	130mu	D 3652

Features

The reinforced fiberglass yarn provides the filament tapes high tensile strength; the PET film backing provides excellent abrasion and moisture resistance. The proper packaging-grade adhesive is specially to provide good initial adhesion & long-term holding power.

Little knowledge for tape application:

- * The laminated adhesion depends on the contact area therefore a proper pressure & time helps improve the adhesion strength.
- * The substrates should be clean without oil, clean using solvents when necessary.
- * The best laminate temperature is room temperature; it becomes hard when temperature approach 0°C as the adhesive film becomes firm.

Suggested Uses

- * Use for Difficult substrates or 2 different types of substrates.
- * Wide environment temperature range.
- * sealing for furniture door and windows in construction.
- * Lamination of difficult substrates.

Storage:

- * First-in-first-out.
 - * Store in cool, dry place without sunshine.
 - * Storage life: 2 years from the date of ma king.
-

The above data and the statement are based on our best knowledge and experiments. And it is for reference only. We do not guarantee the suitability of our above-mentioned product(s) for your specific uses. It is a must that the users conduct proper tests to ensure the suitability of our product for users' specific purposes before practical uses.

**GuangZhou Weasy Adhesive Products Co.,Ltd**

Tel: 86-20-22086997
Fax: 86-20-22086918
Contact person: Vincent
M: +86-13922104457
Mail: Vincent@weasytapes.com

Web:<http://www.weasytapes.com/en/>