

PET double sided Tape

PT0306-50200



Technical Data Sheet

Product Description

transparent PET double-sided tape, high tensile strength, transparent
* PET film as a substrate, coated on both sides high viscosity, high cohesive strength adhesive double-sided tape.

Product Construction

Backing	Backing Color	Release Paper	Adhesive
PET film	transparent	white	Pressure Sensitive Adhesive

Key Features

- * Ultra-thin: Up to 0.03mm thinnest, can be customized requirement.
- * High viscosity to most common smooth substrate.
- * Soft and black PET film has good shading performance.
- * Environmental: environmentally materials

Typical Physical Properties

(21 Degree, stainless steel)

Note: Typical data for reference, not for specification purpose.

		Testing method
Peel adhesion at 180°:	>50N/25mm	D 3330
Holding Power:	>72h	D 3654
Thickness:	200um	D 3652
Initial Adhesion	13#	
Temperature resistance	-20~80	

Little knowledge for tape application:

- * Used for variety substrate bonding, such as metal panel, plastic and films.
- * Ideas for graphic overlays, nameplates, appliques and decoratives trim.
- * Good for mobile phone parts attachment, such as gasket, mesh, insulation films.
- * Fixing of reflection foil to LCD frame.
- * Good for LCD BLU mounting.
- * Good for battery pack mounting.

The above data and the statement are based on our best knowledge and experiments. And it is for reference only. We do not guarantee the suitability of our above-mentioned product(s) for your specific uses. It is a must that the users conduct proper tests to ensure the suitability of our product for users' specific purposes before practical uses.



CQC-1509001 质量认证



GuangZhou Weasy Adhesive Products Co.,Ltd

Tel: 86-20-22086997
Fax: 86-20-22086918
Contact person: Grant
M: +86-13922357380
Mail: sales6@weasytapes.com

Web: <http://www.weasytapes.com>