

# Masking Tapes

GF0307-520



Weasy

## Technical Data Sheet

### Product Description



- \* General Purpose Masking Tape GF0307-520 uses crepe paper as the backing material, which is coated with rubber type adhesive.
- \* Applicable to different temperature resistance with cleaner removal. No adhesive residue.
- \* It is used for fixing resistors, capacitors, masking and automobile industry in the process of spray-painting.

### Product Construction

| Backing    | Backing Color | Reinforce | Adhesive                    |
|------------|---------------|-----------|-----------------------------|
| Crepe pape | Yellow        | None      | Pressure Sensitive Adhesive |

### Typical Physical Properties

(21 Degree, stainless steel)

**Note:** Typical data for reference, not for specification purpose.

|                        |            | Testing method |
|------------------------|------------|----------------|
| Peel adhesion at 180 ° | 6.8N/inch  | D 3330         |
| Tensile Strength:      | 65.3N/inch | D 3759         |
| Elongation at Break:   | 7%         | D 3759         |
| Holding Power:         | >24h       | D 3654         |
| Total Thickness:       | 105mu      | D 3652         |

### Features

1. Has the competence and product assortment to provide with high quality solutions for any of paint masking application.

2.Offers a wide arrange of solutions for paper masking, fineline/design painting, overmasking, and window flange masking.

### Little knowledge for tape application:

- \* The laminated adhesion depends on the contact area therefore a proper pressure & time helps improve the adhesion strength.
- \* The substrates should be clean without oil, clean using solvents when necessary.
- \* The best laminate temperature is room temperature; it becomes hard when temperature approach 0°C as the adhesive film becomes firm.

### Suggested Uses

- \* Use for Difficult substrates or 2 different types of substrates.
- \* Wide environment temperature range.
- \* Lamination of difficult substrates.

---

**Storage:**

- \* First-in-first-out.
  - \* Store in cool, dry place without sunshine.
  - \* Storage life: 2 years from the date of ma king.
- 

The above data and the statement are based on our best knowledge and experiments. And it is for reference only. We do not guarantee the suitability of our above-mentioned product(s) for your specific uses. It is a must that the users conduct proper tests to ensure the suitability of our product for users' specific purposes before practical uses.

**GuangZhou Weasy Adhesive Products Co.,Ltd**

Tel: 86-20-22086997

Fax: 86-20-22086918

Contact person: Grant

M: +86-15011834616 Or +86-13922357380

Mail: sales6@weasytapes.com

Web:<http://www.weasytapes.com>