

Tissue Tape

DS-140



Weasy

Technical Data Sheet

Product Description

- * DS140 is high-performance tissue paper both side coated with hot melt pressure sensitive adhesive and laminated with double side release paper .
- * Remains good adhesion at wide temperature range(depends on the nature and the weight of the sealing materials .
- * The lamination work can be operated in all the natural temperature environments such as winter(above 0°C)and summer(the best operation temperature should be 15-35°C, the lamination operation becomes harder as temperature decrease gradually from room temperature to 0°C,because the glue film become firm). Once laminated(stuck) the laminate adhesion remains well through normal environment temperature.

Product Construction

| Backing | Release Paper | Adhesive |
|--------------|---------------|-----------------------------|
| Tissue paper | white | Pressure Sensitive Adhesive |

Typical Physical Properties

(21 Degree, stainless steel)

Note: Typical data for reference, not for specification purpose.

| | | Testing method |
|------------------------|----------|----------------|
| Peel adhesion at 180°: | 47N/25mm | D 3330 |
| Holding Power: | > 72h | D 3654 |
| Thickness: | 50±5um | D 3652 |
| Temperature resistance | -20~80 | |

Little knowledge for tape application:

- * The laminated adhesion depends on the contact area therefore a proper pressure & time helps improve the adhesion strength.
- * The substrates should be clean without oil, clean using solvents when necessary.
- * The best laminate temperature is room temperature, it becomes hard when temperature approach 0°C as the adhesive film becomes firm..

The above data and the statement are based on our best knowledge and experiments. And it is for reference only. We do not guarantee the suitability of our above-mentioned product(s) for your specific uses. It is a must that the users conduct proper tests to ensure the suitability of our product for users' specific purposes before practical uses.



CQC-1509001质量认证



GuangZhou Weasy Adhesive Products Co.,Ltd

Tel: 86-20-22086997
Fax: 86-20-22086918
Contact person: Grant
M: +86-13922357380
Mail: sales6@weasytapes.com

Web: <http://www.weasytapes.com>